

HIGH EFFICIENCY WATER HEATER READY

CODE

**DO YOU HAVE A PHOTO
OF THIS?**

PLEASE SEND IT TO US!

[installation.feedback@
energycodeace.com](mailto:installation.feedback@energycodeace.com)

Electrical Power

To facilitate the future upgrade to a high efficiency water heater, all water heaters must have 120V receptacle located within 3 feet of the water heater and accessible to the water heater.

Code Reference: 2013 Title 24, Part 6 Standards §150.0(n)

CODE

**DO YOU HAVE A PHOTO
OF THIS?**

PLEASE SEND IT TO US!

[installation.feedback@
energycodeace.com](mailto:installation.feedback@energycodeace.com)

Venting

To facilitate the future upgrade to a high efficiency water heater, all water heaters must have either a Category III or IV vent, or a Type B vent that is straight with no bends (to facilitate easy upgrade to a Category III or IV).

Code Reference: 2013 Title 24, Part 6 Standards §150.0(n)

CODE

**DO YOU HAVE A PHOTO
OF THIS?**

PLEASE SEND IT TO US!

[installation.feedback@
energycodeace.com](mailto:installation.feedback@energycodeace.com)

Condensate Drain

To facilitate the future upgrade to a high efficiency water heater, all water heaters must have either a Category III or IV vent, or a Type B vent that is straight with no bends (to facilitate easy upgrade to a Category III or IV).

Code Reference: 2013 Title 24, Part 6 Standards §150.0(n)

CODE

**DO YOU HAVE A PHOTO
OF THIS?**

PLEASE SEND IT TO US!

[installation.feedback@
energycodeace.com](mailto:installation.feedback@energycodeace.com)

Gas Supply Line

To facilitate the future upgrade to a high efficiency water heater, all water heaters must have a gas supply line with a capacity of at least 200,000 Btu/h. This typically requires a ¾" pipe, while most water heaters usually only get a ½" pipe.

Code Reference: 2013 Title 24, Part 6 Standards §150.0(n)

Plumbing

HIGH EFFICIENCY WATER HEATER READY

Notes:
